

CLOPAY COMMERCIAL – MODEL 3722

**energy series** with intellicore®



Model 3722, 22'2" x 14' Doors; Shown with 24" x 8" Lites

CONSTRUCTION	STEEL	EFFICIENCY	WARRANTY
2" THICKNESS	20 GAUGE	18.4 R-VALUE	10YR LIMITED CONSTRUCTION



## POLYURETHANE INSULATED FLUSH STEEL DOORS

Clopay Model 3722 is for commercial and industrial facilities where demanding conditions require a rugged door that is also energy efficient.

- **Intellicore®** insulation provides the highest energy efficiency, while remaining environmentally friendly.
- **Steel-Sandwich Construction** enhances durability and strength.
- **3-Stage Paint Process** delivers a virtually maintenance-free finish.
- **Thermal Break** enhances insulating properties for extreme energy efficiency.
- **Optional Accessories** add functionality while complementing the building.



Panels are preprimed inside and out to inhibit rust. Hot-dipped, galvanized steel is painted with primer and given a tough oven-baked polyester top coat to provide the most rust-resistant steel door available. Ten-year warranty against rust-through.

[clopaycommercial.com](http://clopaycommercial.com)

## PANEL DESIGN



Flush

## COLOR OPTIONS



Standard White

Chocolate

Due to the printing process, colors may vary.

## CUSTOM PAINT OPTION



Color Blast® offers more than 1,500 Sherwin-Williams® color options to complement your building design. This durable two-part paint system has been thoroughly tested and is backed by a five-year warranty.

Due to solar reflective formulation to meet greater than a 38 LRV, some colors may not be available.

## FEATURES

### STANDARD HARDWARE

18 gauge single-end stiles; 16 gauge double-end stiles

PVC vinyl astragal with aluminum retainer

Commercial 10-ball steel rollers (nylon tires available)

Steel step plate and lift handle

Heavy-duty galvanized end stiles

Inside slide lock for increased security

19 gauge steel hinge support plates

2" (50.8 mm) or 3" (76.2 mm) track

10,000 cycle springs

Galvanized aircraft cable with minimum 7:1 safety factor

Variety of track configurations to meet building specifications

### MATERIALS AND CONSTRUCTION

Panel Thickness 2" (50.8 mm)

Insulation CFC and HCFC-free Intellicore® polyurethane

R-value 18.4\*

Thermal Break Continuous foam

Exterior Steel 20 gauge (.034" min.) (.86 mm)

Interior Steel 28 gauge (.015" min.) (.38 mm)

Exterior Surface Stucco embossed, flush

Max Width 36'2" (11 m)

Max Height 24' (7.3 m)

Exterior Colors Standard White and Chocolate. Also available in Color Blast®.

Interior Color Standard White

Limited Warranties 10-Year delamination  
10-Year rust-through  
1-Year material and workmanship

\*Calculated door section R-value is in accordance with DASMA TDS-163.

For special sizes, applications and options, consult Commercial Information Assistance (CIA) at 1-800-526-4301.

## ADDITIONAL OPTIONS

### WINDOW OPTIONS



24" x 8"



24" x 12"



Full-View




26" x 13"

Available with nominal insulated, nominal insulated tempered or tempered glass. Full-view section, pre-painted Standard White or Chocolate; glazing options include DSB, tempered, plexiglass, insulated, insulated tempered and polycarbonate. 26" x 13" (66.04 cm x 33.02 cm) windows are available with Lexan® or plexiglass.

### HEAVY-DUTY HARDWARE (where not standard)



Double-end hinge



3" Track



High performance hardware features 10 gauge end hinges, heavy-duty top bracket and 3" sealed roller with 5/8" stem.

### MULLIONS



Carry-away, roll-away or swing-up mullions are available on select sizes.

### BREAK-AWAY SECTION



Single section and double sections available on select sizes.

### PASS DOOR



32" wide x 80" high (.81 m x 2.3 m), max 16'2" (4.9 m) wide section.

### EXHAUST PORT



Can be cut into any type of sectional door. Available in select sizes.



WindCode® doors are available in many sizes and pressure ratings.



Upgrade your standard door with industrial-grade components.

### HIGH CYCLE SPRINGS



25,000, 50,000 or 100,000 cycle springs available.

### CODE COMPLIANT

This Clopay door complies with the 2015 IECC (International Energy Conservation Code) with an air infiltration rating of .40 cfm/ft<sup>2</sup> or less (IECC, Section 402.5.2), and also meets the U-factor requirement of .37 or less (IECC, Section C402.4, for Climate Zones 1 through 8).



For more information on these and other Clopay products, call 1-800-526-4301 or visit [clopaycommercial.com](http://clopaycommercial.com)



©2018 Clopay Building Products Company, Inc., a Griffon company.



CMDC-3722-07\_REV0518